

TECHNICAL DATA SHEET

Document no#: - 100720191100

<u>Date</u>	:	10.07.2019
<u>Document type</u>	:	Technical Document
<u>Item</u>	:	Trefoil clamp
<u>Material & finish options</u>	:	Stainless Steel AISI 304(A2) / 316 (A4) / HDG steel EN 1461
<u>Technical specifications</u>	:	Dimensions of the trefoil clamp will be defined according to the cable diameters. Rubber gasket optional for stainless steel. HDG finish supplied without rubber gasket.

For Low Voltage Conductors:

Part No:	T	W2	W1	A	L	Bolt
TGWS-TC-300-L	2	29	58	40	113	M6x20
TGWS-TC-400-L	2	33	66	40	115	M6x20
TGWS-TC-500-L	2	38	76	40	125	M6x20
TGWS-TC-630-L	2	42	84	40	135	M6x20
TGWS-TC-800-L	2	50	100	40	160	M6x20
TGWS-TC-1000-L	2	55	110	40	195	M8x20
TGWS-TC-1200-L	2	60	120	40	230	M8x20

For Medium Voltage Conductors:

Part No:	T	W2	W1	A	L	Bolt
TGWS-TC-300-M	3	36	72	40	142	M8x20
TGWS-TC-400-M	3	40	80	40	150	M8x20
TGWS-TC-500-M	3	43	86	40	156	M10x20
TGWS-TC-630-M	3	47	94	40	164	M10x20
TGWS-TC-800-M	3	53	106	40	176	M10x20
TGWS-TC-1000-M	3	60	120	40	190	M10x20
TGWS-TC-1200-M	3	71	142	40	212	M12X20

For High Voltage Conductors:

Part No:	T	W2	W1	A	L	Bolt
TGWS-TC-300-H	4	63	126	40	225	M8x20
TGWS-TC-400-H	4	66	132	40	230	M8x20
TGWS-TC-500-H	4	70	140	40	240	M10x20
TGWS-TC-630-H	4	75	150	40	250	M10x20
TGWS-TC-800-H	4	79	158	40	260	M10x20
TGWS-TC-1000-H	4	84	168	40	270	M10x20
TGWS-TC-1200-H	4	90	180	40	280	M12X20
TGWS-TC-1600-H	4	95	190	40	290	M12x20
TGWS-TC-2000-H	4	102	204	40	305	M12x20

Image :

